

Gaco Western

S I N C E 1 9 5 5

Product Data Sheet:

GacoFlex U-5651

October 2014

Supersedes 1/00

GACOFLEX® U5651 POLYURETHANE ACCELERATOR

- DESCRIPTION:** GacoFlex U5651 is an accelerator for two-component polyurethanes.
- USAGE:** GacoFlex U5651 is for use as an additive to increase the cure rate of GacoFlex two-component polyurethanes. GacoFlex U5651 should be added to the Polyol (Part A) side only.
- STANDARD COLOR:** Clear

APPLIED PRODUCT DATA

- FLASH POINT:** ASTM D-56 (Tag closed cup) 81° F
- BOILING RANGE:** 280° - 288° F
- VAPOR DENSITY:** Air = 1: Heavier
- SOLIDS:** Weight: 60%
Volume: 53.30%
- STORAGE STABILITY:** Six months in unopened containers stores at 50°F to 85°F (10°C to 29°C)

APPLICATION

- MIXING:** Mix GacoFlex U5651 into the Polyol side (Part A) of GacoFlex two-component polyurethanes. Contact Gaco Western for quantity of U5651 accelerator to be used.
- POT LIFE:** Addition of GacoFlex U5651 will shorten the pot life of the two-component system. Reduction of pot life will vary based on amount of accelerator added and the environmental conditions that exist during mixing.
- CURE TIME:** Addition of GacoFlex U5651 will also increase the rate of cure and should be used only as specifically instructed by Gaco Western.

For specific Safety and Health information please refer to Material Safety Data Sheet.

